



INSTALLATION INSTRUCTIONS

E-CF LED Series

Document:	CI308X46R1	Date	2014-3--11
Created By:	TMT	DCR#	2014-069



E-CF2L



E-CF3L

CAUTIONS

IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:

READ AND FOLLOW ALL SAFETY INSTRUCTIONS

1. Turn off power supply to avoid the risk of electrical shock.
2. This product must be wired in accordance with the National Electrical Code or applicable local codes and ordinances. Proper grounding is required to ensure personal safety. A qualified electrician should do all work.
3. For supply wire temperature rating, refer to fixture label.
4. Only use in 120 – 270 Volt applications.

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

TO AIM FIXTURE

1. Loosen the side bolt connected to the arm knuckle to aim the fixture up or down. Re-tighten bolt to secure the fixture in the desired position.
2. For a rain-tight seal, caulk the aiming arm joint, top and sides of the canopy with silicone caulking compound.

INSTALLATION

1. Thread the floodlight mounting arm into the 1/2" opening of the cover and secure it with 1/2" locknut.

FIXTURE WIRING

1. Connect the black fixture lead to the voltage supply lead with customer supplied wire connector.
2. Connect the white fixture lead to the neutral supply lead with the customer supplied wire connector.
3. Connect the green or green/yellow or bare copper ground lead to the supply ground lead with the customer supplied wire connector.