

Applications: Security, perimeter, entryways, and walkway lighting.

PRODUCTS THAT MEET **BUY AMERICAN** REQUIREMENTS WITHIN ARRA ARE DESIGNATED BY THIS SYMBOL.



Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Initial Delivered Lumens	CCT
E-BR2M07QM(*)	70-watt Pulse Start Metal Halide (PSMH)	120/208/240/277-volt HX ballast HPF	E26	Clear, medium base	32.7 lbs.	5600	65 CRI
E-BR2M10QM(*)	100-watt Pulse Start Metal Halide (PSMH)	120/208/240/277-volt HX ballast HPF	E26	Clear, medium base	33.6 lbs.	9000	65 CRI
E-BR2H07QM(*)	70-watt High Pressure Sodium (HPS)	120/208/240/277-volt HX ballast HPF	E26	Clear, medium base	32.5 lbs.	6000	22 CRI
E-BR2F42UM(*)	42-watt Compact Fluorescent (CFL)	120- to 277-volt Universal Electronic	-	Coated, GX24q-4 base	27.6 lbs.	3190	82 CRI

(*) Specify 180° Shielded Lens option: A-180°

Construction & Materials

- Extruded aluminum housing supplied internally with a formed and channeled 16 gauge steel frame
- Two silicone lens seals prevent moisture from entering the lens
- Clear, super-durable polycarbonate lens with specular reflector
- Template and anchor bolts included
- E-coat epoxy primer with five layers of protection
- Super durable medium-bronze powder topcoat

Performance

- 5-year finish warranty
- 3-year fixture warranty
- 1-year lamp warranty

Electrical

Regulatory

- UL Listed
- Suitable for wet locations
- Assembled in the USA

Accessories

Internal Louver



CAT.# E-BR/LVRK
(Black)

Aesthetically appealing louver eliminates uplight and glare. The aluminum louver simply rests on the reflector inside the lens. DeltaGuard finish supplied with black, acrylic powder topcoat. Shipped as a one piece unit, consisting of five individual louvers with 40 degree tilt, held by three vertical posts spaced at 120 degrees.