

LED BOLLARD 27-WATT LED (E-BR3L SERIES)

Applications: Security, entryway, walkway and perimeter.



CREE®
LEDs

7.87" Dia x 36.06" H
Weight: 15.2 lbs.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹	Comparable To
E-BR3L27U4K	27W LED, Neutral White	120V-277V	1675	4000K	72	91%	50W MH
E-BR3L27U5K	27W LED, Cool White	120V-277V	1330	5000K	83	91%	50W MH

¹ Calculated L₇₀ based on 9,576 hours of LM-80 testing: >57,500 hours

Performance

- 57,500 hours of maintenance-free operation to L₇₀ at 25°C (77°F)
- Minimum starting temperature: -20°C (-4°F)
- 5-year limited warranty

Construction & Materials

- Durable aluminum housing
- Metallic black powder coat
- Polycarbonate lens
- Mounts to the included anchor bolts
- Cree® LEDs inside

Electrical

- ERP non-dimming driver
- > 0.9 power factor
- < 20% total harmonic distribution
- Universal voltage (120V-277V)

Regulatory

- ETL Listed for wet locations



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com