


LOW-PROFILE LED CANOPY LIGHT - MEDIUM DISTRIBUTION 42-WATT LED (E-CP2L04CS)

Applications: Security, entryway and perimeter lighting. Also recommended for parking garages, shopping area walkways, and exterior canopies
Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 1 to 2 times the mounting height



12"D x 12"W x 2.375"H
Weight: 7.5 lbs.



LED PATTERN



This fixture is listed on the Design Lights Consortium® Qualified Products List.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹	Comparable To:
E-CP2L04CS	42W LED Cool White	120V-277V	4100	5000K	≤ 70	50,000 Hours	100W PSMH

¹ Calculated L₇₀ based on 6,048 hours of LM-80 testing: >36,000 hours

Line Current Data

Voltage	Operating Amperes
120V	0.35
208V	0.21
240V	0.18
277V	0.16



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com

LOW-PROFILE LED CANOPY LIGHT - MEDIUM DISTRIBUTION

42-WATT LED (E-CP2L04CS)

Performance

- 50,000 hours of maintenance-free operation to L₇₀
- Minimum starting temperature: -22° F
- 5-year limited warranty

Construction & Materials


- Rugged and durable aluminum housing
- Silver polyester powder-coat finish
- UV-stabilized acrylic lens with molded precision optics
- 1/2" conduit entries on top for pendant mounting
- Slots provided on top for mounting over a 4" square or octagonal J-box
- Cree® LEDs inside

Electrical

- 0-10 Dimmable Driver (see below for recommended dimmers)
- Universal voltage (120V through 277V)

Regulatory

- ETL Listed for wet locations



E-CP2L04CS fixture mounted at 12 feet with 0° tilt.

Recommended Dimmers

- Lutron CTCL-153PDH-WH
- Lutron TGCL-153PH-WH
- Lutron MA-600MR-WH
- Leviton R50-1PLOG-10M

NOTE: The presence of a dimmer on this chart is not a guarantee or warranty of the compatibility of the fixture in any particular installation. The absence of a dimmer from this chart does not necessarily imply incompatibility.



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com