

Applications: Security, pathway and perimeter lighting; ideal for entry ways, walkways, and parking facilities.

Typical Mounting Height: 8 to 20 feet **Typical Spacing:** 2 to 3 times the mounting height

PRODUCTS THAT MEET **BUY AMERICAN**
REQUIREMENTS WITHIN ARRA
ARE DESIGNATED BY THIS SYMBOL.



3"D x 8"W x 8"H
Lamp Included

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Initial Delivered Lumens	CCT
E-CS1F211W(*) (120V)	21-watt Compact Fluorescent (CFL)	120V Electronic	-	Coated, GR10q-4 base	3.4 lbs.	1350	82 CRI
E-CS1F212W(*) (277V)	21-watt Compact Fluorescent (CFL)	277V Electronic	-	Coated, GR10q-4 base	3.4 lbs.	1350	82 CRI

(*) Specify with photocell option. P=Photocell

Performance

- 5-year finish warranty
- 3-year fixture warranty
- 1-year lamp warranty

Construction & Materials

- Meets Americans with Disability Act Accessibility Guidelines (ADAAG)
- Translucent polycarbonate lens
- Knockouts are provided for 1/2" conduit entry, mounting over single gang J-box, 4" square or 4" octagonal J-boxes

Electrical

Regulatory

- UL Listed
- Suitable for wet locations
- Assembled in the USA