

Applications: Security, pathway and perimeter lighting; ideal for entry ways, walkways, and parking facilities.

Typical Mounting Height: 8 to 20 feet **Typical Spacing:** 2 to 3 times the mounting height

PRODUCTS THAT MEET BUY AMERICAN REQUIREMENTS WITHIN ARRA ARE DESIGNATED BY THIS SYMBOL.



3.875" D x 10" W x 10" H
Lamp Included

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Initial Delivered Lumens	CCT
E-CS2F28UW	28-watt Compact Fluorescent (CFL)	120V-277V Universal Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2045	82 CRI
E-CS2F281WP (120V photocell)	28-watt Compact Fluorescent (CFL)	120V Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2045	82 CRI
E-CS2F282WP (277V photocell)	28-watt Compact Fluorescent (CFL)	120V Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2045	82 CRI
E-CS2F38UW	38-watt Compact Fluorescent (CFL)	120V-277V Universal Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2845	82 CRI
E-CS2F381WP (120V photocell)	38-watt Compact Fluorescent (CFL)	277V Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2845	82 CRI
E-CS2F382WP (277V photocell)	38-watt Compact Fluorescent (CFL)	277V Electronic	-	Coated, GR10q-4 base	5.4 lbs.	2845	82 CRI

Performance

- 5-year finish warranty
- 3-year fixture warranty
- 1-year lamp warranty

Construction & Materials

- Meets Americans with Disability Act Accessibility Guidelines (ADAAG)
- Translucent polycarbonate lens
- Knockouts are provided for 1/2" conduit entry, mounting over single gang J-box, 4" square or 4" octagonal J-boxes

Electrical

Regulatory

- UL Listed
- Suitable for wet locations
- Assembled in the USA