

Applications: Security, entryway and perimeter lighting. Also recommended for parking garages, shopping area walkways, and exterior canopies
Typical Mounting Height: 8 to 25 feet **Typical Spacing:** 1 to 1.5 times the mounting height



PRODUCTS THAT MEET BUY AMERICAN REQUIREMENTS WITHIN ARRA ARE DESIGNATED BY THIS SYMBOL.



12" D x 12" W x 5" H
Lamp Included

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Initial Delivered Lumens	CCT
E-CS3M07QW	70-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V HX ballast HPF	E26	Clear, medium base	16.1 lbs.	5600	65 CRI
E-CS3M10QW	100-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V HX ballast HPF	E26	Clear, medium base	16.9 lbs.	9000	65 CRI
E-CS3P15QW ¹	150-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V HX ballast HPF	E26	Clear, medium base	18.6 lbs.	14000	68 CRI
E-CS3F42UW ²	26/32/42-watt Compact Fluorescent	Universal Electronic	GX24q-3 GX24q-4	-	10.7 lbs.	-	-

¹Lamp ordered separately. Socket accepts lamps with GX24q-3 and GX24q-4 base. Ballast accepts 26/32/42W lamp.

²Surface Box accessory (see next page) is required for 150W PSMH if mounting to combustible surface.

Construction & Materials

- Durable and seamless die-cast aluminum housing with super durable white powder topcoat
- Fixture is designed for direct mount over a recessed junction box
- Two 1/2" conduit openings provided for wire supply
- Surface Box is required for 150W PSMH when mounting to combustible surface such as plaster or drywall
- Lens assembly consists of rigid aluminum frame and high-impact, #P73 crystal tempered glass
- Specular aluminum reflector
- E-coat epoxy primer with five layers of protection

Performance

- 5-year finish warranty
- 3-year fixture warranty
- 1-year lamp warranty

Electrical

Regulatory

- UL Listed
- Suitable for wet locations
- Assembled in the USA

Accessories



SURFACE BOX
CAT.# E-CS3&4/SMBK
 For use where surface wiring is required. Five threaded and closed 1/2" conduit entries for surface wiring.



WIRE GUARD
CAT.# E-CS3/WG