


# PARKING ROADWAY AREA LIGHT (E-FR SERIES)

**Applications:** Roadway, parking areas or for building-mounted security lighting  
**Typical Mounting Height:** 15 to 30 feet **Typical Spacing:** 3 to 5 times the mounting height



Shown with  
6" arm



"A"	"B"
12" (305 mm) Square	5.0" (127 mm)
16" (406 mm) Square	6.5" (165 mm)
22" (559 mm) Square	9.3" (235 mm)

SEPARATE MOUNTING OPTIONS	
	E-ACC12M 1-1/2" Arm for 12" Housing E-ACC16M 1-1/2" Arm for 16" & 22" Housings
	E-ACE12M 6" Arm for 12" Housing E-ACE16M 6" Arm for 16" & 22" Housings
	E-ACE12M12 12" Arm for 12" Housing E-ACE16M12 12" Arm for 16" & 22" Housings
	E-ACUY U-bracket for 12" & 16" Housings (Not for 22" housings)

Catalog # 2" Adjustable Fitter	Catalog # No Mounting Hardware	Wattage	Housing Size
E-FR1P15SQM	E-FR1P15QM	150W PSMH	12"
E-FR2P25SQM	E-FR2P25QM	250W PSMH	16"
E-FR2P32SQM	E-FR2P32QM	320W PSMH	16"
E-FR2P40SQM	E-FR2P40QM	400W PSMH	16"
E-FR3M99SQM	E-FR3M99QM	1000W MH	22"
E-FR1H15SQM	E-FR1H15QM	150W HPS	12"
E-FR2H25SQM	E-FR2H25QM	250W HPS	16"
E-FR2H40SQM	E-FR2H40QM	400W HPS	16"

### Performance

- 5-year finish warranty. 3-year fixture warranty. 1-year lamp warranty.


### Construction & Materials

- 120/208/240/277V HPF ballast
- Seamless, die-cast aluminum housing
- Rigid aluminum frame with high-impact tempered glass lens

### Electrical

### Regulatory

- UL Listed
- Suitable for wet locations



Distribution  
Pattern



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96<sup>th</sup> Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | [www.e-conolight.com](http://www.e-conolight.com)

# PARKING ROADWAY AREA LIGHT (E-FR SERIES)

## Accessories



**Wire Guard**  
CAT.# E-ACWG12 -12" Housing  
CAT.# E-ACWG16 -16" Housing  
CAT.# E-ACWG22 -22" Housing



**Backlight Shield**  
CAT.# E-ACBLS12 -12" Housing  
CAT.# E-ACBLS16 -16" Housing  
CAT.# E-ACBLS22 -22" Housing



**Button Photocell (For 2" Fitter)**  
CAT.# E-ACP1 -120V(n/a 1000W)  
CAT.# E-ACP2 - 208/240/277V



**Wood Pole Mounting Bracket**  
(For use with yoke mount)  
CAT.# E-ACWPMBM



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96<sup>th</sup> Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | [www.e-conolight.com](http://www.e-conolight.com)