


# STANDARD FLOODLIGHT (E-FS SERIES)

**Applications:** Roadway, parking areas or for building-mounted security lighting  
**Typical Mounting Height:** 15 to 30 feet **Typical Spacing:** 3 to 5 times the mounting height



Shown with 2" adjustable fitter



"A"	"B"
12" (305 mm) Square	5.0" (127 mm)
16" (406 mm) Square	6.5" (165 mm)
22" (559 mm) Square	9.3" (235 mm)

Catalog # 2" Adjustable Fitter	Catalog # Yoke Mount	Wattage	Housing Size
E-FS1P15SQM	E-FS1P15YQM	150W PSMH	12"
E-FS2P25SQM	E-FS2P25YQM	250W PSMH	16"
E-FS2P32SQM	E-FS2P32YQM	320W PSMH	16"
E-FS2P40SQM	E-FS2P40YQM	400W PSMH	16"
E-FS3M99SQM	E-FS3M99YQM	1000W MH	22"
E-FS1H15SQM	E-FS1H15YQM	150W HPS	12"
E-FS2H25SQM	E-FS2H25YQM	250W HPS	16"
E-FS2H40SQM	E-FS2H40YQM	400W HPS	16"

## Performance

- 5-year finish warranty. 3-year fixture warranty. 1-year lamp warranty.


## Construction & Materials

- 120/208/240/277V HPF ballast
- Seamless, die-cast aluminum housing
- Rigid aluminum frame with high-impact tempered glass lens

## Electrical

## Regulatory

- UL Listed
- Suitable for wet locations



Distribution  
Pattern



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96<sup>th</sup> Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | [www.e-conolight.com](http://www.e-conolight.com)

**Accessories**



**Deep Baffle**  
CAT.# E-ACDB12 -12" Housing  
CAT.# E-ACDB16 -16" Housing



**Wire Guard**  
CAT.# E-ACWG12 -12" Housing  
CAT.# E-ACWG16 -16" Housing



**Wood Pole Mounting Bracket**  
(For use with yoke mount)  
CAT.# E-ACWPMBM



**Button Photocell (For 2" Fitter)**  
CAT.# E-ACP1 -120V  
CAT.# E-ACP2 - 208/240/277V



**Polycarbonate Vandal Shield**  
CAT.# E-ACLS12 -12" Housing  
CAT.# E-ACLS16 -16" Housing  
CAT.# E-ACLS22 -22" Housing



**Glare Shield**  
CAT.# E-ACGS12 -12" Housing  
CAT.# E-ACGS16 -16" Housing