


FLAT BACK LINE VOLTAGE TRACK (E-KFB_R SERIES)


Applications: For general purpose track lighting in indoor commercial, retail, or industrial applications.




E-KFB2R*
White Finish




E-KFB3R*
Black Finish



E-KFB3RS*
White Finish



E-KFB4R*
Black Finish



Catalog #	Description	Voltage	Lamp (not included)	Aiming
E-KFB2R*	Flat back line voltage track fixture	Line voltage Halogen- medium base	PAR20 Max. 50W	Tilt: Approx. 135° Rotation: 358°
E-KFB3R*	Flat back line voltage long neck track fixture	Line voltage Halogen- medium base	PAR30L Max. 75W	Tilt: Approx. 135° Rotation: 358°
E-KFB3RSW	Flat back line voltage short neck track fixture	Line voltage Halogen- medium base	PAR30 Max. 75W	Tilt: Approx. 135° Rotation: 358°
E-KFB4R*	Flat back line voltage track fixture	Line voltage Halogen- medium base	PAR38 Max. 150W	Tilt: Approx. 135° Rotation: 358°

(*) Specify finish color. K=Black, W=White

Performance

- 1-year limited warranty

Construction & Materials

- Deep-drawn steel round back housing
- Polyester powder coated finish
- Comes standard with an internal baffle in black finish.
- Compatible with 1 or 2 circuit track
- This classic shape utilizes has a U-shaped double yoke with a single-locking knob to secure the aiming angle

Mounting

- UL Listed for use with existing Ruud Lighting T1 & T2 and Juno® T & TU systems (not affiliated with e-conolight)

Regulatory

- UL and cUL Listed
- Suitable for dry locations



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com