


Applications: Security, pathway and perimeter lighting; ideal for entry ways, walkways, and corridors.
Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 2 to 3 times the mounting height

PRODUCTS THAT MEET **BUY AMERICAN**
REQUIREMENTS WITHIN ARRA
ARE DESIGNATED BY THIS SYMBOL.



Lamp Included



"A"	"B"
8" Sq.	4.1"

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Initial Delivered Lumens	CCT
E-SS1M07QM	70-watt Pulse Start Metal Halide (PSMH)	120/208/240/277-volt HX ballast NPF	E26	Clear, medium base	9.9 lbs.	5600	65 CRI

Construction & Materials

- Durable die-cast aluminum housing
- Knockouts provided on back of housing for 1/2" conduit entry, mounting over a 4" square or octagonal, and single gang J-boxes
- 1/2" NPT threaded hubs on three sides for conduit entry
- Neoprene gasket on back of housing provides a watertight mounting seal
- Sponge cord gasket between housing and lens ensures a watertight seal
- White polycarbonate lens held in place with hidden spring clip assembly
- E-coat epoxy primer with five layers of protection
- Super durable medium-bronze powder topcoat


Performance

- 5-year finish warranty
- 3-year fixture warranty
- 1-year lamp warranty

Electrical

Regulatory

- UL Listed
- Suitable for wet locations
- Assembled in the USA



E-SS1 fixture ceiling mounted
at 12 feet with 0° tilt.

Accessories

Surface Mounting Box




CAT.# E-SR/SMBZ
(Dark Bronze)



CAT.# E-SR/SMBM
(Medium Bronze)

Die-cast aluminum in medium or dark bronze finish. For use where surface wiring is required. Five tapped and plugged knockouts to feed 1/2" conduit. 10" x 6" x 1.25".

Surface Mounting Box with Photocell



CAT.# E-SR/SMB1ZP
(Dark Bronze, 120V)



CAT.# E-SR/SMB1MP
(Medium Bronze, 120V)

CAT.# E-SR/SMB2ZP
(Dark Bronze, 208V-277V)

CAT.# E-SR/SMB2MP
(Medium Bronze, 208V-277V)

Same as Surface Mounting Box but includes installed photocell.