

5" & 6" LED RECESSED RETROFIT KIT 14-WATT LED (E-T6C SERIES)

Applications: For use in a variety of existing 5" and 6" recessed housings, comparable to 75W PAR30.



7.5" Trim Width x 2.75" H
Weight: 0.7 lbs.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹
E-T6C1143WW †	13.4W LED	120V	730	3000K	91	35,000 Hours

† Recessed housing not included

¹ Calculated L₇₀ based on 6,048 hours of LM-80 testing: >36,000 hours

Performance

- Estimated 35,000 hours of maintenance-free operation
- 5-year limited warranty

Construction & Materials

- Edison-style socket adaptor included
- Compatible with most 5" and 6" incandescent recessed housings
- Easy installation with push in retention clips
- Durable construction with integrated trim
- Cree® LEDs inside

Electrical

- Dimmable to 10% with most standard dimmers (see below for compatible dimmers)
- 120 voltage

Regulatory

- UL Listed for wet locations
- Suitable for use in IC-rated housings

Recommended Dimmers

- Pass & Seymour DLV703P
- Cooper SLC03P-W-K
- Leviton R50-IP06-10M

NOTE: The presence of a dimmer on this chart is not a guarantee or warranty of the compatibility of the fixture in any particular installation. The absence of a dimmer from this chart does not necessarily imply incompatibility.

Accessories



GU24 Socket Adaptor
CAT.# E-T6C-GU24

Title 24 compliant with GU24 socket adaptor



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com