

5" & 6" LED RECESSED RETROFIT KIT 13-WATT & 17-WATT LED (E-T6C2 SERIES)

Applications: For use in a variety of existing 5" and 6" recessed housings



7.5" Trim Width x 2.75" H
Weight: 0.7 lbs.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	Estimated Lifetime ¹	Comparable To
E-T6C2132WW	13W LED Soft White	120V	966	2700K	93	60,000 Hours	75W Incandescent
E-T6C2133WW	13W LED Warm White	120V	966	3000K	93	60,000 Hours	75W Incandescent
E-T6C2172WW	17W LED Soft White	120V	1273	2700K	93	60,000 Hours	100W Incandescent
E-T6C2173WW	17W LED Warm White	120V	1273	3000K	93	60,000 Hours	100W Incandescent

Recessed housing not included

¹ Calculated L₇₀ based on 10,000 hours of LM-80 testing: >60000 hours

Performance

- Estimated 60,000 hours of maintenance-free operation to L₇₀ at 25°C (77°F)
- Minimum starting temperature: -10°C (-50°F)
- 5-year limited warranty

Construction & Materials

- Trim: Spun aluminum
- Housing: ABS plastic
- White powder-coat finish for extra corrosion protection and long-lasting color
- Polycarbonate lens
- Adjustable torsion spring clips allow for easy installation into most 5" and 6" recessed housings
- Edison-style socket adaptor included

Electrical

- Dimmable (see next page for recommended dimmers)
- 120V Operation
- Amperage Draw: 0.11A at 120V (13W)
0.15A at 120V (17W)
- > 0.9 power factor
- < 20% total harmonic distortion (13W)
< 21% total harmonic distortion (17W)

Regulatory

- UL Listed for wet locations



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com

5" & 6" LED RECESSED RETROFIT KIT 13-WATT & 17-WATT LED (E-T6C2 SERIES)

Accessories



GU24 Socket Adaptor

CAT.# E-T6C-GU24

Title 24 compliant with GU24 socket adaptor

Recommended Dimmers

- Lutron TGCL153PH-WH
- Leviton 6631
- Cooper SLC03P-W-K

NOTE: The presence of a dimmer on this chart is not a guarantee or warranty of the compatibility of the fixture in any particular installation. The absence of a dimmer from this chart does not necessarily imply incompatibility.



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com