

TRADITIONAL-STYLE LED SURFACE MOUNT WRAP 36-WATT & 71-WATT LED (E-WR2 & E-WR4 SERIES)

Applications: Storage, laundry rooms, utility lighting, work space



36W: 49.0"L x 8.5"W x 2.5"H
Weight: 8.75 lbs.
71W: 49.0"L x 11.0"W x 2.5"H
Weight: 12.0 lbs.

Catalog #	Description	Input Voltage	Initial Delivered Lumens	CCT	CRI	50K Hours Projected Lumen Maintenance Factor at 25°C ¹
E-WR2L3641	36W LED, Neutral White	120V	2590	4000K	> 85	92.98%
E-WR4L7141	71W LED, Neutral White	120V	4911	4000K	> 85	92.98%

¹ Calculated L₇₀ based on 10,000 hours of LM-80 testing; >60,000 hours

Performance

- TM-21 estimated lifetime is >60,000 hours to L₇₀ at 25°C (77°F)
- -18°C (-0.4°F) minimum starting temperature
- 5-year limited warranty

Construction & Materials

- Constructed of durable 20-gauge steel
- White powder coat finish
- Clear prismatic acrylic lens
- Surface mount

Electrical

- 120V
- Non-dimmable
- Amperage Draw: 2-Lamp - 0.34A
4-Lamp - 0.68A
- > 0.9 power factor
- < 20% total harmonic distribution
- 16-gauge minimum supply wire required

Regulatory

- UL Listed for dry locations



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com