

CHICAGO APPROVED REMOTES HEADS (E-X1H SERIES)

Applications: For general purpose emergency lighting in indoor & outdoor commercial, retail, or industrial applications.



Weight:
1.85 lbs.



Wet Location
Weight:
1.85 lbs.



Weight:
1.1 lbs.



Wet Location
Weight:
1.15 lbs.



All "Chicago Approved" exit & emergency lighting offered by e-conolight are UL-listed for damp locations and meet city requirements as outlined in the City Code of Ordinances.

Catalog #	Description	Color	Weight
E-X1H11206	Remote Head, indoor, single, 6V, 12-Watt	White	1.1lbs.
E-X1H21206	Remote Head, indoor, double, 6V, 12-Watt	White	1.85 lbs.
E-X1H11212	Remote Head, indoor, single, 12V, 12-Watt	White	1.1lbs.
E-X1H21212	Remote Head, indoor, double, 12V, 12-Watt	White	1.85 lbs.
E-X1H11206W	Remote Head, outdoor wet location, single, 6V, 12-Watt	Gray	1.15lbs.
E-X1H21206W	Remote Head, outdoor wet location, double, 6V, 12-Watt	Gray	1.85 lbs.
E-X1H11212W	Remote Head, outdoor wet location, single, 12V, 12-Watt	Gray	1.15lbs.
E-X1H21212W	Remote Head, outdoor wet location, double, 12V, 12-Watt	Gray	1.85 lbs.



WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com

Performance

- 5-year limited warranty on housing and electronics

Construction & Materials

- Wedge-base incandescent lamps
- Universal mounting plate and mounting hardware included
- Housings are 5VA flame retardant injection molded thermoplastic

Electrical

Regulatory

- Suitable for wall or ceiling mount



Due to continuous product improvement, information in this document is subject to change. All published photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. Fixture photometry was completed on a single representative fixture. Actual production units may vary up to ±10% of initial delivered lumens. Lumen maintenance values at 25°C (77°F) are calculated per TM-21 based on LM-80 data and in-situ fixture testing.

1501 96th Street, Sturtevant, WI 53177 | Phone (888)243-9445 | Fax (262)504-5409 | www.e-conolight.com