

INSTALLATION INSTRUCTIONS E-WC & E-WG LED LIGHT

Document:	LPN00270X0001A0_A	Date	2014-8-20
Created By:	TMT	DCR#	2014-303



E-WC



E-WG

WALL MOUNTING

NOTE: Make sure to seal the top and sides of the canopy with silicone-base sealant after installation.

1. Fixtures are mounted using a crossbar and universal nipple attached to a customer supplied junction box. Screw the crossbar into the junction box using (2) supplied screws. See **Figure 1**.
2. Thread nipple into crossbar. See **Figure 1**.
3. Make electrical connections as following and carefully push wires into junction box:
 - Connect the Line to Black
 - Neutral to White
 - Ground to Green screw located on crossbar
4. Making sure that no wires are pinched place fixture over nipple and secure using the supplied acorn nut. See **Figure 1**.

CAUTIONS

IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:

READ AND FOLLOW ALL SAFETY INSTRUCTIONS

1. To reduce the risk of electrical shock, turn off power supply before installation or servicing.
2. This luminaire must be installed in accordance with the NEC or your local electrical code. If you are not familiar with these codes and requirements, consult a qualified electrician.

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

FIGURE 1

