

C-EE-A-CHI-EX-SFC-SF/DF Series

Chicago-Approved LED Exit/Stair Sign



RELIABILITY WHEN YOU NEED IT MOST

Our C-Lite Chicago-Approved LED Exit/Stair Sign can run either 120V or 277V. It features a battery backup option and comes with a 5-year limited warranty. Choose from single face or double face, each of which includes 1 or 2 glass panels, respectively.



PRODUCT SPECIFICATIONS

OVERVIEW

- Input Power: 5W
- Operating Temperature Range: 32°F to 122°F (0°C to 50°C)
- Limited Warranty: 5 Years*
- Meets UL924, NFPA 101 Life Safety Code, NEC & OSHA codes
- UL Listed

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none"> • 5W LED Exit/Stair (Single or Double Face) with 6" red letters and white housing • Battery Backup or AC only options available • Chicago-Approved and UL Listed • Mounting hardware included 	<ul style="list-style-type: none"> • Exit/Stair Identification • Indoor commercial, retail & industrial applications in the City of Chicago 	<ul style="list-style-type: none"> • 120V or 277V Operation

ORDERING INFORMATION

Example: C-EE-A-CHI-EX-SFC-SF-RED-BB-WH

C-EE	A	CHI		SFC		RED		WH
PRODUCT	SERIES	CITY	IDENTIFICATION	MOUNTING	SINGLE/ DOUBLE FACE	LETTER COLOR	BATTERY BACKUP	HOUSING FINISH COLOR
C-EE	A	CHI	EX Exit Identification STR Stair Identification	SFC Surface Mount	SF Single Face DF Double Face	RED Red Letters	BB Battery Backup AC AC Only	WH White

CERTIFICATIONS



C-EE-A-CHI-EX-SFC-SF/DF Series

SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT
(C-EE-A-CHI-EX-SFC-SF C-EE-A-CHI-EX-SFC-DF) 12-3/8" W x 11-1/4" H x 2-3/8" D	7.5 lbs (AC Version) 8 lbs (BB Version)
(C-EE-A-CHI-GP-EXIT C-EE-A-CHI-GP-STAIR) 12" W x 8-7/8" H x 3/32" D (Glass Panel Inset)	1 lbs

FIXTURE SPECIFICATIONS

HOUSING	Durable, powder-coated 20 gauge steel construction
LENS ASSEMBLY	Tempered glass identification panels
MOUNTING	Mounting canopy included for top or end mount Universal knockout pattern on backplate for wall mount

ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L70 LIFETIME @ 25°C (77°F)	
32°F to 122°F (0°C to 50°C)	>50,000 hours	
SYSTEM WATTS (120-277V)	CURRENT DRAW (AMPS)	
	120V	277V
5W	0.042A	0.02A

WARRANTY AND CERTIFICATIONS

WARRANTY	UL LISTED
5 Year Limited*	Damp Locations

 **CA RESIDENTS WARNING:** Cancer and Reproductive Harm - www.p65warnings.ca.gov

C-EE-A-CHI-EX-SFC-SF/DF Series

ACCESSORIES

	CHICAGO APPROVED GLASS PANEL EXIT RIGHT ARROW
	SKU: C-EE-A-CHI-GP-EXIT-R USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL EXIT DOUBLE ARROW
	SKU: C-EE-A-CHI-GP-EXIT-LR USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL EXIT LEFT ARROW
	SKU: C-EE-A-CHI-GP-EXIT-L USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL EXIT NO ARROW
	SKU: C-EE-A-CHI-GP-EXIT USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL STAIR RIGHT ARROW
	SKU: C-EE-A-CHI-GP-STAIR-R USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL STAIR DOUBLE ARROW
	SKU: C-EE-A-CHI-GP-STAIR-LR USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL STAIR LEFT ARROW
	SKU: C-EE-A-CHI-GP-STAIR-L USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only
	CHICAGO APPROVED GLASS PANEL STAIR NO ARROW
	SKU: C-EE-A-CHI-GP-STAIR USE: With C-EE-A-CHI-EX-SFC-SF/DF and C-EE-A-CHI-STR-SFC-SF/DF Series Only

© 2021 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. Due to continuous product improvement, information in this document is subject to change. The UL logo is a registered trademark of UL LLC.