

C-TR-A-BT14 Series

LED Architectural Basket Troffer - 1' x 4'

Replaces 2 x F17T8 | 1 x F32T8 (33L), 3 x F17T8 | 2 x F32T8 (45L)

C-LITE
LED LIGHTING

HIGH EFFICIENCY, LIGHT WEIGHT DESIGN, EASY INSTALL

Our Architectural LED Basket Troffers have a way of making everything underneath them look better. But, this isn't by accident - it's because of their exceptionally high CRI. They're a cost saving LED solution that deliver energy savings benefits while also offering an attractive design that blends into any ceiling. They're really easy to install, have a cETLus Listing and are backed by our 5-year warranty.



PRODUCT SPECIFICATIONS

OVERVIEW

- Initial Delivered Lumens: 3300L or 4500L
- CRI: ≥ 80
- CCT: Warm White 3500K, Neutral White 4000K, Cool White 5000K
- Mounting: Recessed
- Input Power: 26W or 35W
- Dimmable: 0-10V dimming to 10%
- Operating Temperature Range: -4°F to 104° (-20°C to 40°C)
- Lifespan L_{70} AT 25°C (77°F): Estimated >100,000 Hours
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Limited Warranty: 5-Years*
- Replaces 2 x F32T8

FEATURES	BENEFITS	RECOMMENDED USE
<ul style="list-style-type: none">• Pre-installed driver• Powder coated aluminum frame• Opaque white acrylic lens	<ul style="list-style-type: none">• An easy-to-install upgrade from linear fluorescent lighting• Delivers optimal performance with up to 129 lumens per watt• Fully tested and backed by Cree Lighting®	<ul style="list-style-type: none">• Offices• Educational & Retail• Commercial & Institutional


ORDERING INFORMATION

Example: C-TR-A-BT14-33L-35K-WH

C-TR	A	BT14			WH	
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	CCT	COLOR	OPTIONS
C-TR	A	BT14 LED Architectural Basket Troffer 1' x 4'	33L 3300 Lumens 26W 45L 4500 Lumens 35W	35K Warm White (3500K) 40K Neutral White (4000K) 50K Cool White (5000K)	WH White	EB Integrated Emergency Back Up Driver - Provides 90 minutes of emergency operation - 3170 (33L) or 3210 (45L) lumens in emergency mode - Maximum mounting height: 15' (4.6m)

CERTIFICATIONS:

C-TR-A-BT14 Series



SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
47-3/4" L x 11-3/4" W x 2-3/4" H	10.4 lbs.	8 to 12 feet	8' x 8' – 10' x 10'

FIXTURE SPECIFICATIONS

HOUSING	Durable steel construction White polyester powder-coat finish
LENS ASSEMBLY	Precision engineered acrylic lens and polystyrene diffuser prevents hot spots, shadows and glare, while providing uniform illumination
MOUNTING	Recessed Installs into conventional grid ceiling Pre-installed driver

ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	LIFESPAN L ₇₀ AT 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION	DIMMABLE
-4°F to 104° (-20°C to 40°C)	Estimated >100,000 Hours	> 0.9 at full load	< 20% at full load	0-10V dimming to 10%


LUMEN PACKAGE	SYSTEM WATTS (120-277V)	CURRENT DRAW (AMPS)			
		120V	208V	240V	277V
33L	26	0.22A	0.13A	0.11A	0.09A
45L	35	0.29A	0.17A	0.15A	0.13A

WARRANTY & CERTIFICATIONS

WARRANTY	ETL LISTED	DLC
5-Year Limited*	Damp Locations	—

C-TR-A-BT14 Series

ACCESSORIES

	DRYWALL GRID ADAPTER
	<p>SKU: DGA14-WHT (single-pack) DGA14-WHT-10PK (10-pack)</p> <p>USE: For use when mounting in drywall ceilings</p>

© 2023 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cETLus Listed Intertek logo is a trademark of Intertek Testing Services NA, Inc.