

## C-TR-A-BT22 Series

LED Architectural Basket Troffer - 2' x 2'

Replaces 2 x F17T8 | 1 x F32T8/U6 (33 L) & 3 x F17T8 | 2 x F32T8/U6 (45 L)

**C-LITE**  
LED LIGHTING

### HIGH EFFICIENCY, LIGHT WEIGHT DESIGN, EASY INSTALL

Our Architectural LED Basket Troffers have a way of making everything underneath them look better. But, this isn't by accident - it's because of their exceptionally high CRI. They're a cost saving LED solution that deliver energy savings benefits while also offering an attractive design that blends into any ceiling. They're really easy to install, have a cETLus Listing and are backed by our 5-year warranty.



### PRODUCT SPECIFICATIONS

#### OVERVIEW

- Initial Delivered Lumens: 3300L or 4500L
- CRI:  $\geq 80$
- CCT: Warm White 3500K, Neutral White 4000K, Cool White 5000K
- Mounting: Recessed
- Input Power: 26W or 35W
- Dimmable: 0-10V dimming to 10%
- Operating Temperature Range: -4°F to 104° (-20°C to 40°C)
- Lifespan  $L_{70}$  AT 25°C (77°F): Estimated >100,000 Hours
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Limited Warranty: 5-Years\*
- Replaces 2 x F17T8 | 1 x F32T8/U6 (33 L) & 3 x F17T8 | 2 x F32T8/U6 (45 L)

FEATURES	BENEFITS	RECOMMENDED USE
<ul style="list-style-type: none"><li>• Pre-installed driver</li><li>• Powder coated aluminum frame</li><li>• Opaque white acrylic lens</li></ul>	<ul style="list-style-type: none"><li>• An easy-to-install upgrade from linear fluorescent lighting</li><li>• Delivers optimal performance with up to 129 lumens per watt</li><li>• Fully tested and backed by Cree Lighting®</li></ul>	<ul style="list-style-type: none"><li>• Offices</li><li>• Educational &amp; Retail</li><li>• Commercial &amp; Institutional</li></ul>

### ORDERING INFORMATION

Example: C-TR-A-BT22-33L-35K-WH

C-TR	A	BT22			WH	
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	CCT	COLOR	OPTIONS
C-TR	A	BT22 LED Architectural Basket Troffer 2' x 2'	<b>33L</b> 3300 Lumens 26W <b>45L</b> 4500 Lumens 35W	<b>35K</b> Warm White (3500K) <b>40K</b> Neutral White (4000K) <b>50K</b> Cool White (5000K)	WH White	<b>EB</b> Integrated Emergency Back Up Driver - Provides 90 minutes of emergency operation - 3170 (33L) or 3210 (45L) lumens in emergency mode - Maximum mounting height: 15' (4.6m)



**CA RESIDENTS WARNING:** Cancer and Reproductive Harm –  
[www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)


Rev. Date: V4 02/24/2023

For informational purposes only. Content is subject to change. \*See [creelighting.com/resources/warranties](http://creelighting.com/resources/warranties)

#### CERTIFICATIONS:



# C-TR-A-BT22 Series



## SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
23-3/4" L x 23-3/4" W x 2-3/4" H	8.0 lbs.	8 to 15 feet	8' x 8' – 10' x 10'

## FIXTURE SPECIFICATIONS

HOUSING	Durable aluminum construction White polyester powder-coat Sealed, maintenance-free fixture design
LENS ASSEMBLY	Precision engineered acrylic lens and polystyrene diffuser prevents hot spots, shadows and glare, while providing uniform illumination
MOUNTING	Recessed Installs into conventional grid ceiling Pre-installed driver

## ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	LIFESPAN L <sub>70</sub> AT 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION	DIMMABLE
-4°F to 104° (-20°C to 40°C)	Estimated >100,000 Hours	> 0.9 at full load	< 20% at full load	0-10V dimming to 10%


LUMEN PACKAGE	SYSTEM WATTS (120-277V)	CURRENT DRAW (AMPS)			
		120V	208V	240V	277V
33L	26	0.22A	0.13A	0.11A	0.09A
45L	35	0.29A	0.17A	0.15A	0.13A

## WARRANTY & CERTIFICATIONS

WARRANTY	ETL LISTED	DLC
5-Year Limited*	Damp Locations	—

# C-TR-A-BT22 Series

## ACCESSORIES

	DRYWALL GRID ADAPTER
	<p>SKU: <b>DGA22-WHT</b> (single-pack) <b>DGA22-WHT-10PK</b> (10-pack)</p> <p>USE: For use when mounting in drywall ceilings</p>

© 2023 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent [www.creelighting.com/patents](http://www.creelighting.com/patents). C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cETLus Listed Intertek logo is a trademark of Intertek Testing Services NA, Inc.

