

C-VT-C-LIN4 Series

4-foot Linear LED Vapor Tight

Replaces: 2-Lamp T8 32W or 2-Lamp - T5HO 54W

C-LITE
LED LIGHTING

RELIABLE VAPOR TIGHTS YOU CAN COUNT ON

cULus Listed, our C-Lite 4-foot LED Linear Vapor Tight delivers up to 8300 lumens and is available in either 4000K or 5000K. It features continuous poured gasket along with 12 acetal plastic latches to ensure tight waterproof seal, tool-less entry into the housing, and a diffused polycarbonate lens for even and efficient light distribution. Enjoy an easy installation and 5-year limited warranty.



PRODUCT SPECIFICATIONS

OVERVIEW

- CRI: 70+
- CCT: 4000K or 5000K
- Input Power: 54W **(8L)**; 34W **(5L)**
- Dimmable: 0-10V to 10%
- IP65 Rated
- Estimated L70 Lifetime @ 25°C: >100,000 hours
- Operating Temperature Range: -40°F to 104°F (-40°C - 40°C)
- Power Factor: > .9
- Total Harmonic Distortion: < 20%
- Limited Warranty: 5-Year*
- Replaces: 2-Lamp T8 32W **(5L)**; 2-Lamp - T5HO 54W **(8L)**

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none">• Surpassed IP65 product testing (makes the product completely dust-tight with protection against low-pressure water jets from any direction).• Continuous poured gasket for optimal water tight housing• Tool-less entry into housing to help with easy installation• Diffused lens to help hide light source and distribute light most efficiently	<ul style="list-style-type: none">• Entryways• Parking garage structures• Storage facilities	<ul style="list-style-type: none">• Universal (120V - 277V)

ORDERING INFORMATION

Example SKU: C-VT-C-LIN4-5L-50K-UL-WH


C-VT	C	LIN4			UL	WH
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	CCT	VOLTAGE	COLOR
C-VT	C	LIN4 4-foot	5L 5300 Lumens 8L 8300 Lumens	40K Neutral White (4000K) 50K Cool White (5000K)	UL Universal 120-277V	WH White

CERTIFICATIONS:

 **CA RESIDENTS WARNING:** Cancer and Reproductive Harm –
www.p65warnings.ca.gov



C-VT-C-LIN4 Series



SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT
47-3/8" L x 5" W x 3-1/8" H	6.06 lbs.	0 to 15 feet

FIXTURE SPECIFICATIONS

HOUSING	White, high-impact polycarbonate
LENS ASSEMBLY	Integrated diffused polycarbonate lens for even and efficient light distribution
MOUNTING	Includes hardware for surface mounting

LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
-40°F to - 104°F (-40°C to 40°C)	> 100,000 Hours	> .9	< 20%

SKU	REPLACES	LUMEN OUTPUT	BUG RATINGS*	SYSTEM WATTS	CURRENT DRAW (AMPS)			
					120V	208V	240V	277V
C-VT-C-LIN4-5L-40K-UL-WH	2-Lamp - T8 32W	5300 Lumens	B2-U3-G2	34W	0.29	0.17	0.14	0.13
C-VT-C-LIN4-5L-50K-UL-WH								
C-VT-C-LIN4-8L-40K-UL-WH	2-Lamp - T5HO 54W	8300 Lumens	B3-U3-G2	54W	0.44	0.25	0.22	0.19
C-VT-C-LIN4-8L-50K-UL-WH								

* For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt.

WARRANTY AND CERTIFICATIONS


WARRANTY	cULus LISTED	DLC
5-Year Warranty*	Wet Listed	—

C-VT-C-LIN4 Series

ISO PLOT CHART


C-VT-C-LIN4-5L-50K

Mounting Height: 12' AFG



C-VT-C-LIN4-8L-50K

Mounting Height: 12' AFG



Note: All published photometric testing performed to IES LM-79 standards. Fixture photometry was completed on a single representative fixture. Foot candle levels are noted inside graph.