



NOCTURA SERIES SELECTION GUIDE

Area, Flood and Wall Mount

CREE  **LIGHTING**

NOCTURA™ LED AREA

The Noctura™ LED Area luminaire minimizes cost of ownership with easy installation, high performance and quality backed by Cree Lighting. The Noctura Series has a coordinated style across area, flood and wall mount luminaires to provide a consistent daytime appearance across a building site or campus. Versatile mounting configurations offer installation flexibility and ease of application for direct pole, tenon or vertical flat surface mounting.

Applications: Ideal for both retrofit and new installation: parking area, security, or site pathway applications.



10kV SURGE SUPPRESSION PROTECTION

5 YEAR LIMITED WARRANTY

	Replaces Up To	Cree Lighting Solution	Initial Delivered Lumens	Voltage	CCT
AREA	Metal Halide				
	250W	NTA-A-NM-Optic-11L-CCT-Voltage-BZ	11,000	120-277V or 347-480V	4000K, 5000K
	400W	NTA-A-NM-Optic-19L-CCT-Voltage-BZ	19,000		
	1000W	NTA-A-NM-Optic-35L-CCT-Voltage-BZ	35,000		
	Pulse Start Metal Halide				
	250W	NTA-A-NM-Optic-11L-CCT-Voltage-BZ	11,000	120-277V or 347-480V	4000K, 5000K
	400W	NTA-A-NM-Optic-19L-CCT-Voltage-BZ	19,000		
	1000W	NTA-A-NM-Optic-35L-CCT-Voltage-BZ	35,000		
	High Pressure Sodium (HPS)				
	250W	NTA-A-NM-Optic-11L-CCT-Voltage-BZ	11,000	120-277V or 347-480V	4000K, 5000K
	400W	NTA-A-NM-Optic-19L-CCT-Voltage-BZ	19,000		
	400W	NTA-A-NM-Optic-35L-CCT-Voltage-BZ	35,000		
WALL MOUNT	Metal Halide				
	50W	NTW-A-NM-T3-1L-CCT-Voltage-BZ	1,600	120-277V or 347-480V	4000K, 5000K
	100W	NTW-A-NM-T3-3L-CCT-Voltage-BZ	3,500		
	175W	NTW-A-NM-T3-7L-CCT-Voltage-BZ	7,000		
	250W	NTW-A-NM-T3-11L-CCT-Voltage-BZ	11,000		
	400W	NTW-A-NM-T3-17L-CCT-Voltage-BZ	17,000		
	Pulse Start Metal Halide				
	100W	NTW-A-NM-T3-3L-CCT-Voltage-BZ	3,500	120-277V or 347-480V	4000K, 5000K
	150W	NTW-A-NM-T3-7L-CCT-Voltage-BZ	7,000		
	250W	NTW-A-NM-T3-11L-CCT-Voltage-BZ	11,000		
	400W	NTW-A-NM-T3-23L-CCT-Voltage-BZ	23,000		
	High Pressure Sodium (HPS)				
	50W	NTW-A-NM-T3-1L-CCT-Voltage-BZ	1,600	120-277V or 347-480V	4000K, 5000K
	100W	NTW-A-NM-T3-3L-CCT-Voltage-BZ	3,500		
	150W	NTW-A-NM-T3-7L-CCT-Voltage-BZ	7,000		
	200W/250W	NTW-A-NM-T3-11L-CCT-Voltage-BZ	11,000		
	400W	NTW-A-NM-T3-23L-CCT-Voltage-BZ	23,000		

NOCTURA™ WALL MOUNT

The Noctura™ LED Wall Mount luminaire minimizes cost of ownership with easy installation, high performance and quality backed by Cree Lighting. The rugged yet lightweight aluminum housing and mounting box are designed for easy installation of a variety of junction box styles (4" square, 3" and 4" octagonal, single gang (vertical or horizontal mounts). Luminaires (1L & 3L) allow for through-wired or conduit entry from the top, sides and rear. Luminaires (7L and higher) allow for through-wired or conduit entry from the top, bottom, sides and rear.

Applications: Ideal for both retrofit and new installation, building facade, security and general lighting.



LED Wall Mount

10kV

**SURGE
SUPPRESSION
PROTECTION**

**5 YEAR
LIMITED
WARRANTY**

Optics	Wattage	Mounts	Controls
Type III Medium	75W	Direct Arm Mount: NTA-DA-BZ; Extended Arm: NTX-3R-BZ Adjustable Arm Mount: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mount: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	NEMA® 3-Pin Photocell Receptacle
Type IV Medium	130W		
Type V Medium	230W		
Type III Medium	75W	Direct Arm Mount: NTA-DA-BZ; Extended Arm: NTX-3R-BZ Adjustable Arm Mount: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mount: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	NEMA® 3-Pin Photocell Receptacle
Type IV Medium	130W		
Type V Medium	230W		
Type III Medium	75W	Direct Arm Mount: NTA-DA-BZ; Extended Arm: NTX-3R-BZ Adjustable Arm Mount: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mount: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	NEMA® 3-Pin Photocell Receptacle
Type IV Medium	130W		
Type V Medium	230W		
Type III Medium	12	Wall Mount	Knockout for field installed button photocell
	24		
	46		
	74		
	111		
Type III Medium	24	Wall Mount	Knockout for field installed button photocell/A
	46		
	74		
	148		
Type III Medium	12	Wall Mount	Knockout for field installed button photocell
	24		
	46		
	74		
	148		

NOCTURA™ LED FLOOD

The Noctura™ LED Flood luminaire minimizes cost of ownership with easy installation, high performance and quality backed by Cree Lighting. The Noctura Series has a coordinated style across area, flood and wall mount luminaires to provide a consistent daytime appearance across a building site or campus. Versatile mounting configurations offer installation flexibility and ease of application for ground, direct pole, tenon or vertical flat surface mounting.

Applications: Ideal for both retrofit and new installation, accent, sign or facade lighting applications.



	Replaces Up To	Cree Lighting Solution	Initial Delivered Lumens	Voltage	CCT
FLOOD	METAL HALIDE				
	50W	NTF-A-NM-Optic-1L-CCT-Voltage-BZ	1,600	120-277V or 347-480V	4000K, 5000K
	70W	NTF-A-NM-Optic-3L-CCT-Voltage-BZ	3,000		
	175W	NTF-A-NM-Optic-6L-CCT-Voltage-BZ	6,500		
	250W	NTF-A-NM-Optic-10L-CCT-Voltage-BZ	10,000		
	400W	NTF-A-NM-Optic-14L-CCT-Voltage-BZ	14,000		
	PULSE START METAL HALIDE				
	100W	NTF-A-NM-Optic-3L-CCT-Voltage-BZ	3,000	120-277V or 347-480V	4000K, 5000K
	150W	NTF-A-NM-Optic-6L-CCT-Voltage-BZ	6,500		
	250W	NTF-A-NM-Optic-10L-CCT-Voltage-BZ	10,000		
	320W	NTF-A-NM-Optic-14L-CCT-Voltage-BZ	14,000		
	400W	NTF-A-NM-Optic-21L-CCT-Voltage-BZ	21,500		
	400W	NTF-A-NM-Optic-28L-CCT-Voltage-BZ	28,400		
	HIGH PRESSURE SODIUM (HPS)				
	50W	NTF-A-NM-Optic-1L-CCT-Voltage-BZ	1,600	120-277V or 347-480V	4000K, 5000K
	100W	NTF-A-NM-Optic-3L-CCT-Voltage-BZ	3,000		
	150W	NTF-A-NM-Optic-6L-CCT-Voltage-BZ	6,500		
	200W	NTF-A-NM-Optic-10L-CCT-Voltage-BZ	10,000		
	250W	NTF-A-NM-Optic-14L-CCT-Voltage-BZ	14,000		
	400W	NTF-A-NM-Optic-21L-CCT-Voltage-BZ	21,500		
	400W	NTF-A-NM-Optic-28L-CCT-Voltage-BZ	28,400		



LED Flood 1L



LED Flood 28L



LED Flood with Top Visor




Optics	Wattage	Mounts	Controls
NEMA 4x4 NEMA 6x6	12W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-1L-BZ	Knockout for field-installed button photocell (120-277V only)
	21W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-3L-BZ	
	40W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-6L-BZ	Knockout for field-installed button photocell (120-277V or 347-480V)
	64W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-10L-BZ	
	93W	Adjustable Arm Mounts: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mounts: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	NEMA® 3-Pin Photocell Receptacle
NEMA 4x4 NEMA 6x6	21W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-3L-BZ	Knockout for field-installed button photocell (120-277V only)
	40W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-6L-BZ	Knockout for field-installed button photocell (120-277V or 347-480V)
	64W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-10L-BZ	
	93W	Adjustable Arm Mounts: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mounts: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	Knockout for field-installed button photocell (120-277V or 347-480V) NEMA® 3-Pin Photocell Receptacle
	140W		
	186W		
NEMA 4x4 NEMA 6x6	12W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-1L-BZ	Knockout for field-installed button photocell (120-277V only)
	21W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-3L-BZ	
	40W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-6L-BZ	Knockout for field-installed button photocell (120-277V or 347-480V)
	64W	Knuckle Mount: NTF-KN-BZ, Yoke Mount: NTF-YM-10L-BZ	
	93W	Adjustable Arm Mounts: NTX-AA-BZ; NTX-AA-3R-BZ; Extended Arm: NTX-3R-BZ Trunnion Mounts: NTX-TR-BZ; NTX-TR-3R-BZ; NTX-TR-PK-BZ; Extended Arm: NTX-3R-BZ	Knockout for field-installed button photocell (120-277V or 347-480V) NEMA® 3-Pin Photocell Receptacle
	140W		
	186W		

NOCTURA SERIES

WHATEVER THE MIX, WE HAVE THE MATCH


Finding the right mounting has never been a “one-size-fits-all” lighting challenge. But it often becomes a “one-size-fits-all” frustration. When specific housings are paired with specific mountings and sold as single units, it can be difficult to find the exact fit you need. And that can mean settling for lighting that’s less than ideal. The Noctura Series puts an end to this. Housings and mountings are sold separately—allowing you to mix and match them in order to find the exact combination you need for any location. This modular system puts you in control of delivering what the application needs.

NOCTURA™ LED FLOOD



QUICK CONNECT WIRING

Designed with the installer in mind, the quick connect wiring feature allows for a easier installation. The housing supply cord has a convenient male end connector that twists and locks in with the female end connector supplied with the mount.




LED FLOOD
Quick Connect Wiring



LED AREA
Quick Connect Wiring

NOCTURA™ LED AREA





Visit creelighting.com/noctura or contact a Cree Lighting representative to learn more.
info@creelighting.com | 800.236.6800

© 2019 Cree Lighting, A company of IDEAL Industries. All rights reserved. For informational purposes only. Not a warranty or specification. See creelighting.com for specifications. Cree®, and the Cree logo are registered trademarks of Cree, Inc. Noctura™ is a trademark of Cree Lighting, A company of IDEAL INDUSTRIES. The DLC QPL Premium logo is a registered trademark of Efficiency Forward, Inc. NEMA® is a registered trademark of the National Electrical Manufacturers Association.
CAT/CSJ-C039 Rev. Date 12/04/19

CREE  **LIGHTING**
A COMPANY OF [IDEAL INDUSTRIES, INC.](#)