



HID FLOODLIGHT 150/250-WATT (E-HR3P15QZ, E-HR3P25QZ)

Applications – Building facades, displays, uplighting and signs. Also effective as security lighting, for storage areas and commercial sites.

Typical Mounting Height: 15 to 25 feet

Typical Spacing: 2 to 4 times the mounting height



13-3/8"H x 13-3/8"W x 6-7/8"D

SKU	Description	Ballast	Lamp Base	Recommended Lamp	Weight	Lamp Output	Lamp Color
E-HR3P15QZ	150-Watt Pulse Start Metal Halide (PSMH) HID Floodlight	120/208/240/277V HX ballast HPF	E26	Mogul Base (~PS150E)	17 Pounds	14000 lumens	68 CRI
E-HR3P25QZ	250-Watt Pulse Start Metal Halide (PSMH) HID Floodlight	120/208/240/277V CWA ballast HPF	E39	Mogul Base (Lamp not included)	21.5 Pounds	22000 lumens	65 CRI

Features

- Sturdy die-cast aluminum housing and lens frame, with dark-bronze polyester powder-coat finish
- Tempered-glass lens, thermal-shock and impact resistant
- Fixture comes without mounting. (Order E-ACS slip fitter or E-ACU U-bracket)
- UL Listed for wet locations
- 1-year warranty

Accessories



Photocell, field installed, use with E-ACS slip fitter

SKU: E-ACP1 (120 volts)

SKU: E-ACP2 (208/240/277 volts)

Mounting options



Adjustable slip fitter.
Fits over 2-3/8" O.D. pipe
SKU: E-ACS



Adjustable U-bracket, with 30" cord.
2-1/2"H x 5-1/2"W x 6"D
SKU: E-ACU