

E-LB2 Series

16-Inch Low Bay Pulse Start Metal Halide

APPLICATIONS: Warehouses, industrial and retail sites.
TYPICAL MOUNTING HEIGHT: 15 to 25 feet



Specifications

SKU	DESCRIPTION	BALLAST	BASE	LAMP	WEIGHT	OUTPUT	COLOR RENDITION
E-LB2P25Q	250-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	20.8 lbs.	22,000 Lumens	70 CRI
E-LB2P25QQ (QUARTZ OPTION)	250-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	20.8 lbs.	22,000 Lumens	70 CRI
E-LB2P32Q	320-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	22 lbs.	32,000 Lumens	70 CRI
E-LB2P32QQ (QUARTZ OPTION)	320-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	22 lbs.	32,000 Lumens	70 CRI
E-LB2P40Q	400-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	22.5 lbs.	40,000 Lumens	70 CRI
E-LB2P40QQ (QUARTZ OPTION)	400-watt Pulse Start Metal Halide (PSMH) High Bay	120/208/240/277V CWA Ballast HPF	E39	Clear, mogul base	22.5 lbs.	40,000 Lumens	70 CRI

Features

- Sturdy die-cast aluminum housing
- Rugged 4kv porcelain socket
- Wiring compartment with adjustable leveling feature
- 16-inch spun white aluminum reflector
- Includes drop acrylic lens
- Maximum ambient temperature 35°C

- Mount using threaded 3/4" conduit (by others) or with hook & cord accessory kit (see below)
- UL Listed - for damp locations
- 1-year warranty

Note: Meets 2005 NEC code.

Note: Quartz standby option (delay-relay) includes 100W Quartz lamp.

HIGH BAYS & LOW BAYS



Quality Products, Affordably Priced.

E-LB2 Series

Accessories



3/4" Hook with 6-foot Cord and Plug
(straight blade plug)

SKU: **E-2HCP61S** (120-volt)

3/4" Hook with 6-foot Cord and Plug
(Locking type plug)

SKU: **E-2HCP61** (120-volt)

SKU: **E-2HCP62** (277-volt)

SKU: **E-2HCP64** (208 / 240-volt)

3/4" Hook with 6-foot Cord -NO PLUG

SKU: **E-2HC6**

3/4" Hook only

SKU: **E-2HOOK**



Locking-Type Receptacle (3 blade twist lock)
(120V, 3-wire, NEMA L5-15R)

SKU: **E-ACRCPT31** (120-volt)

(277V, 3-wire, NEMA L7-15R)

SKU: **E-ACRCPT32** (277-volt)

(208/240V, 3-wire, NEMA L6-15R)

SKU: **E-ACRCPT34** (208 / 240-volt)



Mounting/Safety Cable
Cable Length: 5-feet, field adjustable

SKU: **E-ACSC5**