

# INSTALLATION INSTRUCTIONS C-WM-A-WLCY AND C-WM-A-WLSP LED LIGHT

Document:	LPN00483X0001A0_A	Date	03-22-2017
Created By:	TMT	DCR#	



C-WM-A-WLCY



C-WM-A-WLSP

## CAUTIONS

### IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:

### READ AND FOLLOW ALL SAFETY INSTRUCTIONS

- DANGER**- Risk of shock- Disconnect power before installation.  
**DANGER – Risque de choc – Couper l'alimentation avant l'installation.**
- This luminaire must be installed in accordance with the NEC or your local electrical code. If you are not familiar with these codes and requirements, consult a qualified electrician.  
*Ce produit doit être installé conformément à NEC ou votre code électrique local. Si vous n'êtes pas familier avec ces codes et ces exigences, veuillez contacter un électricien qualifié.*

### SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

## WALL MOUNTING

**NOTE:** Make sure to seal the top and sides of the canopy with silicone-base sealant after installation.

- Fixtures are mounted using a crossbar and universal nipple attached to a customer supplied junction box. Screw the crossbar into the junction box using (2) supplied screws. See **Figure 1**.
- Thread nipple into crossbar. See **Figure 1**.
- Make electrical connections as following and carefully push wires into junction box:
  - Connect the Line to Black
  - Neutral to White
  - Ground to Green screw located on crossbar
- Making sure that no wires are pinched place fixture over nipple and secure using the supplied acorn nut. See **Figure 1**.

FIGURE 1

