# **E-KXD Series**

LED Flat Back Track Head Replaces 250W Par38 Halogen



# **Brighten Up Your Space in Style**

Use for spotlight displays or flood applications.

#### **Efficient**

- Up to 60% energy savings
- Consistent color, perfect for color-sensitive applications

#### **Recommended Use**

- Retail
- Industrial

#### **Value**

 Includes 20° spot, 30° narrow and 40° wide flood reflectors

## **Input Voltage**

• 120V Operation

#### **Certifications**











# **E-KXD Series**



#### **Series Overview**

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
4-1/2" <b>D</b> x 6" <b>W</b> x 7-1/4" <b>H</b>	2.7 lbs.		

#### **Fixture Specifications**

HOUSING	Die-cast aluminum housing for driver and optics Available in white or black polyester powder-coat finish Integral on/off switch
LENS ASSEMBLY	Polycarbonate adapter with copper conductor
MOUNTING	Spring latch secures light fixture to track ETL Listed for use with e-conolight® E-K1 and E-K2 Series, Ruud Lighting® T1 and T2 Series and Juno® (not affiliated with e-conolight or Ruud Lighting) T and TU Series track systems only Pivot mount allows up to 315° horizontally and 0-90° vertically in both directions for maximum aiming adjustability

#### **Electrical Performance**

OPERATING MINIMUM	<b>LIFESPAN</b> L <sub>70</sub> at 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC Distortion	DIMMABLE
-20°C (-4°F)	Estimated 35,000 Hours	> 0.9	< 20%	Yes
INPUT VOLTAGE	120V	208V	240V	277V
Current Draw (Amps)	0.3A			

### **Warranty & Certifications**

WARRANTY	ETL LISTED	DLC	ENERGY STAR
3-Year Limited	Dry Locations		

### **Output Specifications**

SKU	LIGHT OUTPUT	<b>COLOR TEMP</b> (See chart)	POWER Consumption	DISTRIBUTION	COLOR ACCURACY
E-KXD235U3K (Black)	2500 Lumens	Warm White (3000K)	36W	Supplied with 20° spot, 30° narrow flood and 40° wide flood reflectors	≥ 80 CRI
E-KXD235U3W (White)	2500 Lumens	Warm White (3000K)	36W		≥ 80 CRI
<b>E-KXD235U7K</b> (Black)	2500 Lumens	Neutral White (4000K)	36W		≥ 80 CRI
E-KXD235U7W (White)	2500 Lumens	Neutral White (4000K)	36W		≥ 80 CRI



CORRELATED **COLOR TEMPERATURE** (CCT)

4000K

3000K

COOL WHITE

NEUTRAL WHITE

WARM WHITE

# **E-KXD Series**

#### **Recommended Dimmers**

- Leviton Trimatron 6683
- Leviton Decora 6633
- Cooper Aspire 9530
- · Lutron Maestro MACL-153M
- Lutron Diva/C-L DVCL-153P-XX
- Lutron Lumea LGCL-153PLH-XX

