

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:



DESCRIPTION

naturaLED® Utility Wrap (UWS) now offers the perfect solution for your lighting needs. The Utility Wrap fixtures are designed for saving energy and easy installation. Available in 27W in two color temperature of 4,000K and 5,000K delivering up to 3,510 lumens with excellent and consistent color. Our Utility Wrap features a full wrap-around UV coated PC plastic prismatic lens and is 48 inches long; designed for junction box installation and works great in parking garages, stairwells, offices, hallways, industrial, commercial and residential, ceiling or wall mounted. This fixture is versatile and efficient.

APPLICATIONS

Conference/Meeting Room, Stairwells, Schools/ Universities, Hospitals, Hotels, Parking Garages

FEATURES

- DLC Premium
- Damp Location
- UL Listed
- Color Temp: 4000K, 5000K
- Voltage: 120-277V, 120-347V
- Input Current: 0.25A
- Powerfactor >0.9
- Beam Angle: Flood
- Dimmable: 1-10V
- CRI: 80
- Operating temperature: -22°F - 122°F
- Lightweight for easy installation
- Excellent thermal design
- Uniform and consistent color
- 5 Year Warranty
- Optional for Purchase: Emergency Driver, Motion Sensor, Lens, Wireguard, Wire Cover

ACCESSORIES



Emergency Driver



Motion/ Daylight Sensor



Wire Cover



Wire Guard



Lens



Surge Protector

SAMPLE NUMBER FXUWS27/48CL/850

FAMILY	SERIES	WATTAGE	LENGTH/LENS	CRI/COLOR TEMP
FX Fixture	UWS Utility Wrap	27 27 Watt	48CL 48" Clear	850 CRI80 5000K



ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Voltage	Damp Location	DLC (S/P)
27	9538	FXUWS27/48CL/840	4000K	3,510	4 x32WT8	120-277V	•	P
27	9539	FXUWS27/48CL/850	5000K	3,510	4 x32WT8	120-277V	•	P
27	9540	FXUWS27/48CL/840/347	4000K	3,510	4 x32WT8	120-347V	•	P
27	9541	FXUWS27/48CL/850/347	5000K	3,510	4 x32WT8	120-347V	•	P

ACCESSORIES (Ordered Separately)

Emergency Driver



Kit- EM with Wireway Cover
K7336197 FXUWS-BAEM-MT
(Emergency Driver Kit)



Emergency Driver only
7336 BAEM4-60BC/MV-A
(4W CEC-Compliant Emergency Driver 120-277V)

Motion/ Daylight Sensor



P10234 SEN-MC605V-D
(Microwave Motion/Photocell Sensor 120-277V)

Wire Guard



P10249 WG-UWS/48/WH
(Wire Guard)



P10197 PLT-UWS/4FT/WH
(Wireway Cover)

Surge Protector



P10389 SPD-L-10KV-277
(10KV Single Phase Surge Protection 120-277V)



P10390 SPD-L-20KV-277
(20KV Single Phase Surge Protection 120-277V)



P10391 SPD-L-20KV-480
(20KV Single Phase Surge Protection 277-480V)


Lens



P10407 LENS-UWS27
(Replacement Lens)


DIMENSIONS

27W (48-inch)
6.88-lbs



PHOTOMETRICS CHART

27W (48-inch)
DLC Premium



Center Beam fc	Beam Width
484 fc	2.9 ft 3.1 ft
128 fc	5.7 ft 6.0 ft
56.0 fc	8.6 ft 9.1 ft
31.2 fc	11.6 ft 12.2 ft
20.3 fc	14.3 ft 15.1 ft
14.0 fc	17.3 ft 18.2 ft

■ Vert. Spread: 81.6°
■ Horiz. Spread: 84.5°

PACKAGE

Case Qty
1 pc

