

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:

DESCRIPTION

naturaLED® cut-off wallpack comes in rugged cast-aluminum housing with excellent thermal design. Our CWP product offers a popular but classic appearance with sleek angle design. Delivering up to 14,667 lumens with different wattages options: 40W, 60W, 80W, 120W. Replacing up to 750-watt metal halide luminaires and provides energy saving up to 72%. Our CWP is ideal for outdoor applications such as carpools, loading areas, driveways, parking areas, and pathways. Suggested for wall mounting minimum above four feet from ground.



**Rated Life 50,000 Hours
Warranty 5 Years**

APPLICATIONS

Security, Pathway, Perimeter, Entryway, Area Lighting, and building facades

FEATURES

- DLC Premium / DLC Standard Qualified
- IP65 Rated
- UL Listed
- Uniform and consistent color
- Material: Die Cast Aluminum
- Input line voltage: 120-277V
- Power Factor: >0.9
- Dimmable: 1-10V
- CRI: 70
- Input current/surge protect level:
 - 40W: 0.34A/4K
 - 60W: 0.52A/4K
 - 80W: 0.68A/4K
 - 120W: 1.00A /6K
- ColorTemp: 4000K, 5000K
- Operating temperature: -40°F - 104°F (-40°C - 40°C)
- Finish Color: Bronze
- 15-30 foot height performance
- Rated 50,000 hours average life

SAMPLE NUMBER LED-FXCWP40/40K/BZ

STYLE	FAMILY	SERIES	WATTAGE	COLOR TEMP	FINISH COLOR
LED	FX Fixture	CWP Cutoff Wallpack	40 40W	40K 4000K	BZ Bronze



CUTOFF WALL PACK

WALL & AREA LUMINAIRES

ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Size	Equiv. Wattage (W)	Dim (V)	IP65 Rated	DLC (S/P)
40	9319	LED-FXCWP40/40K/BZ	4000K	4,861	14.2" x 9.25"	250	1-10V	•	P
40	9320	LED-FXCWP40/50K/BZ	5000K	4,743	14.2" x 9.25"	250	1-10V	•	P
61	9208	LED-FXCWP60/40K/BZ	4000K	7,347	14.2" x 9.25"	400	1-10V	•	P
61	9209	LED-FXCWP60/50K/BZ	5000K	7,482	14.2" x 9.25"	400	1-10V	•	P
80	9443	LED-FXCWP80/40K/BZ	4000K	9,908	14.2" x 9.25"	400-575	1-10V	•	P
80	9444	LED-FXCWP80/50K/BZ	5000K	9,974	14.2" x 9.25"	400-575	1-10V	•	P
120	9445	LED-FXCWP120/40K/BZ	4000K	14,667	14.2" x 9.25"	575-750	1-10V	•	P
120	9446	LED-FXCWP120/50K/BZ	5000K	14,529	14.2" x 9.25"	575-750	1-10V	•	P





DIMENSIONS

40W
6.85-lbs

61W
7.05-lbs

80W
7.48-lbs

120W
10.56-lbs




PHOTOMETRICS CHART

40 Watt
DLC Premium

60 Watt
DLC Premium


80 Watt
DLC Premium

120 Watt
DLC Premium




Center Beam Fc	Beam Width
5.9 ft	11.1 ft
14.2 ft	22.3 ft
6.32 ft	33.4 ft
3.85 ft	44.6 ft
2.27 ft	55.7 ft
1.58 ft	66.8 ft

Vert. Spread: 96.2°
Horiz. Spread: 149.0°




Center Beam Fc	Beam Width
8.5 ft	11.1 ft
21.5 ft	22.2 ft
9.55 ft	33.3 ft
5.37 ft	44.3 ft
3.44 ft	55.4 ft
2.39 ft	66.5 ft

Vert. Spread: 95.9°
Horiz. Spread: 146.8°



Center Beam Fc	Beam Width
11.5 ft	11.4 ft
28.7 ft	22.7 ft
12.7 ft	34.1 ft
7.17 ft	45.5 ft
4.59 ft	56.9 ft
3.18 ft	68.2 ft

Vert. Spread: 97.3°
Horiz. Spread: 151.8°



Center Beam Fc	Beam Width
16.8 ft	11.3 ft
42.1 ft	22.6 ft
18.7 ft	33.8 ft
10.5 ft	45.1 ft
6.73 ft	56.4 ft
4.68 ft	67.7 ft

Vert. Spread: 96.9°
Horiz. Spread: 152.8°

PACKAGE

Case Qty 1 pc

