

ECL2

Slim LED Combo Exit Sign & Emergency Light

Product Description

The NICOR ECL2 Series presents a very slim design, only 1" deep! This UL924 code compliant solution for exit and emergency requirements offers high output and adjustable LED heads to deliver direct illumination for path of egress. The evenly illuminated exit sign is available with red or green stencils. The ECL2 Series offers flexible installation for surface ceiling or wall mount options along with field removable chevrons for universal configuration based on your application's directional needs. Supplied with two faces for single or double face installation.

Construction

- Injection molded thermoplastic ABS housing, UL-94-V-0 rated material
- Adjustable heads for aiming light where required:
 - Vertical head tilt: 330°
 - Horizontal head rotation: 200°

Optical System

- Uniform lighting with specially designed plastic diffuser to prevent shadowing

Electrical

- Operating temperature rating of 5°F to 104°F (-15°C to 40°C)
- Maintenance-free nickel-cadmium battery provides 90-minute emergency operation
 - Recharges in 24 hours
- 120/277VAC Dual voltage operation, 60Hz input
- Fully-illuminated 6" letter height with 3/4" stroke
- Includes test switch/power indicator light

LED

- Light engine provides consistently bright and even EXIT legend illumination with red or green LEDs

Finish

- White textured thermoplastic housing
- Available with either red or green lettering

Installation

- Surface ceiling or wall mount installation options
- Snap-in mounting bracket
- Universal mounting plate with EZ quick connect
- Universal knockout pattern provided on housing for surface mount install
- Field-installable, removable chevron directional indicators for all configurations
- Supplied with two faces for single or double face installation

Compliance

- UL 924
- Listed for damp locations

Warranty

- 2-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

PRODUCT INFORMATION

Input Voltage (V):	120/277 VAC
Power Draw (W):	3.3 W
Emergency Battery:	90 Minutes

Ordering Information

Example: ECL21UNVWHR2

Series	Version	Voltage	Housing Color	Letter Color	Number of Faces
ECL2	1 (Version 1)	UNV (120/277VAC)	WH (White)	G (Green)	2 (Single and Double)
				R (Red)	

Specifications and dimensions subject to change without notice

Project

Catalog

Type

Date

