

LED Slim Wall Pack Replaces Up To 250W MH



## **Security In An Affordable Box**

An affordable option for increasing security at building entrances and around perimeters, our savr E-WPS Series LED Slim Wall Pack delivers up to 8900 lumens. It features a cULus listing, >80 CRI, and a 5-year warranty. Available in 4000K and 5000K.

### **Features & Benefits**

- Sealed, die-cast aluminum housing is weather-proof to prevent the intrusion of dust and water
- Knockouts provided on both sides and bottom for ease of installation
- Slim design offers a sleek and architectural look

### **Recommended Use**

- Security
- Building Entrances
- Perimeter Lighting

### **Input Voltage**

• Universal (120V through 277V Operation)

#### **Certifications**
















#### E-WPS01













#### **E-WPS05**











DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING	
<b>E-WPS01:</b> 6-11/16" L X 5-1/2" W X 3-3/16" D	2.31 lbs.	8-20 Feet	4 to 5 times the mounting height	
<b>E-WPS03:</b> 8" L X 6-1/2"W X 3-3/16" D	2.97 lbs.	8-20 Feet	4 to 5 times the mounting height	
<b>E-WPS05:</b> 10-1/4" L X7-13/16" W X 5" D	5.25 lbs.	8-20 Feet	4 to 5 times the mounting height	
<b>E-WPS08:</b> 11-3/4" L X 9-7/16" W X 5" D	8.25 lbs.	8-25 Feet	4 to 5 times the mounting height	







WARRANTY	5-Year Limited
cULus LISTED	cULus Listed
DLC	Standard

e-conolight/savr/C-Lite:


e-conolight.com | Customer Service: 888-243-9445 | Fax: 262-504-5409 1501 96th Street, Sturtevant, WI 53177

Cree Lighting US / C-Lite Distribution Sales: creelighting.com | Distribution/Sales: 855-617-2733 9201 Washington Avenue, Racine, WI, 53406





OPERATING RANGE		<b>LIFESPAN</b> L70 at 25°C (77°F)		POWER FACTOR		TOTAL HARMONIC DISTORTION		DIMMABLE	
-40°F to 104°F (-40°C to	$A \cap \circ \Gamma_{+} = 1 \cap A \circ \Gamma (A \cap \circ \cap \Gamma_{+} = A \cap \circ \cap )$		Estimated >50,000 Hours > 0.9		<20%		No		
			208V			240V		277V	
E-WPS01	(	).13A		A80.0		0.07A		0.06A	
E-WPS03	(	).25A		0.14A		0.12A		0.11A	
E-WPS05	C	).44A	ı	0.25A		0.22A		0.2A	
E-WPS08	(	).68A		0.39A		0.33A		0.31A	





SKU	REPLACES	LIGHT OUTPUT	COLOR TEMP	POWER CONSUMPTION	COLOR ACCURACY
E-WPS01A-N40B	50W MH	1700 Lumens	4000K	15W	≥ 80
E-WPS01A-N50B	50W MH	1700 Lumens	5000K	15W	≥ 80
E-WPS03A-N40B	100W PSMH	3300 Lumens	4000K	28W	≥ 80
E-WPSO3A-N50B	100W PSMH	3300 Lumens	5000K	28W	≥ 80
E-WPS05A-N40B	150W PSMH	5500 Lumens	4000K	50W	≥ 80
E-WPSO5A-N50B	150W PSMH	5500 Lumens	5000K	50W	≥ 80
E-WPS08A-N40B	250W MH	8900 Lumens	4000K	80W	≥ 80
E-WPSO8A-N50B	250W MH	8900 Lumens	5000K	80W	≥ 80

@ 2020 Cree Lighting, a company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. The savr logo is a trademark of e-conolight, LLC. The cULus logo is a registered trademark of UL LLC.

e-conolight/savr/C-Lite: e-conolight.com | Customer Service: 888-243-9445 | Fax: 262-504-5409 1501 96th Street, Sturtevant, WI 53177 Cree Lighting US / C-Lite Distribution Sales: creelighting.com | Distribution/Sales: 855-617-2733 9201 Washington Avenue, Racine, WI, 53406







Universal Button Photocell (120V-277V)

SKU: JL-423GZ
USE: Photocell is field installed and drilling of the back box is required.

@ 2020 Cree Lighting, a company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. The savr logo is a trademark of e-conolight, LLC. The cULus logo is a registered trademark of UL LLC.

e-conolight/savr/C-Lite: e-conolight.com | Customer Service: 888-243-9445 | Fax: 262-504-5409 1501 96th Street, Sturtevant, WI 53177 Cree Lighting US / C-Lite Distribution Sales: creelighting.com | Distribution/Sales: 855-617-2733 9201 Washington Avenue, Racine, WI, 53406

